

TST200-4 Amplifier

The TST 200-4 is a slim, 1U high amplifier that defies its small size. Outputting 100 watts for each of its stereo channels, the TST 200-4 can easily drive four pairs of 8-ohm speakers in up to four zones thanks to its Thermal Shift Technology™. Each zone can be selected separately from the independent front panel buttons. No more need for a cumbersome speaker selector box. The rear panel includes XLR and RCA inputs, a 12-volt trigger input, signal sensing switches, gain controls, a stereo/mono switch and a subsonic filter for removing low frequency noise that may cause saturation. Optional rack mounting hardware is available for those who choose to include the amp in a custom application.

Don't be content with an ordinary receiver. For little more money you can get Sherbourn's high-end home theater components and really enjoy the power and majesty of a movie soundtrack, the articulation of the human voice, the delicacy of a string quartet—everything is there on all Sherbourn products, thanks to a dedication to innovation, accuracy and performance.



TST200-4 Front



TST200-4 Rear

SPECIFICATIONS: TST200-4 Amplifier

Carton weight	28 lbs.
Number of channels	2
Rated power	100 watts per channel @ 8 ohms with no more than 0.1% THD from 20 Hz-20KHz, all channels driven
Power bandwidth	20Hz-75KHz
Gain	46dB
Signal to noise ratio	90dB/wide band, 105dB A weighted
Line input impedance	20 K ohms
Subsonic filter sensitivity	20Hz and 35Hz
Dynamic headroom	1.3dB
Power supply	120v/60Hz or 230v/50Hz
Dimensions	17.7" W x 14.5" D x 1.75" H

SHERBOURN TECHNOLOGIES, INC.
19-3A Sterling Road
North Billerica, MA 01862 USA
Tel 978.663.7385 Fax 978.663.7389
www.Sherbourn.com

CUSTOM
SOLUTIONS